

# RFC1000-CE

# Wireless RF Transceiver and Repeater

MadgeTech's RFC1000-CE is a wireless transceiver for use with the RFOT and RF2000A Series of data loggers and is CE approved for the European market. The RFC1000-CE transmits to other RFC1000-CEs up to 2500 feet outdoors/line of sight, 700 feet typical indoors/urban. The RFC1000-CE transmits to data loggers up to 2000 feet outdoors/line of sight, 500 feet typical indoors/urban. Additional RFC1000-CEs can be used as repeaters to transmit greater distances or around obstacles.

The RFC1000-CE is designed to communicate between MadgeTech's two-way wireless data loggers and the MadgeTech software and can connect to a maximum of 64 data loggers. Through the use of the software and the RFC1000-CEs, remote data loggers can be started, stopped and downloaded wirelessly. This time saving feature streamlines processes for maximum efficiency.

The RFC1000-CE also includes an external antenna, allowing more flexibility with mounting positions in both orientation and proximity to metal walls. This may be used as a repeater, or directly plugged into the PC.

### **SPECIFICATIONS**

Specifications are subject to change without notice. Specific warranty remedy limitations apply. Call (603) 456-2011 or go to **madgetech.com** for details.

Interface Type	USB (to PC) / Wireless (to Data Logger)	
Materials	ABS plastic (body), PVC plastic (antenna)	
Compatible Data Loggers	RFOT and 2000A Series	
Transmission Distance (to data loggers)	Unobstructed line-of-sight (outdoors): 2,000 ft max.  Typical urban environment (indoors): 500 ft max.	
Transmission Distance (to other RFC1000-CE's)	Unobstructed line-of-sight (outdoors): 2,500 ft max.  Typical urban environment (indoors): 700 ft max.	
RFC Sensitivity	-95 dBm Typical	
Frequency	2.405 GHz - 2.475 GHz	
Operating Environment	-20 °C to +85 °C (-4 °F to +185 °F), 0 %RH to 95 %RH non-condensing	
Dimensions	Enclosure: 3.79 in x 1.57 in x 0.79 in (96.3 mm x 40.0 mm x 20.0 mm) Antenna: 2.71 in (68.8 mm)	
Weight	1.4 oz (40 g)	
Approvals	FCC ID: OA3MRF24J40MC, IC#: 7693A-24J40MC, CE, ETSI 300 328 (EU R&TTE)	



#### **Features**

- Functions as Both a Repeater and a Transceiver
- · Green and Red LED Indicators
- Compatible with MadgeTech's RFOT and 2000A Series Data Loggers

## **Applications**

- · Real-Time Data Logging
- Meat Cooking and Cooling
- Meat Storage
- Smoke Houses
- Food Processing
- Medical Storage
- · Laboratory Monitoring
- Blood Banks
- Hospitals
- Warehouses

# Ordering Information

DEC1000 CE	DN 001300 00	Wireless RF transceiver/repeater CF approved TISR to mini TISR adapter and power supply included
RFC1000-CE	PN 901388-00	Wireless RF transceiver/repeater CE approved. USB to mini USB adapter and power supply included.

■Tel:+86 755-8420 0058 ■Fax:+86 755-2822 5583 ■E-mail:sales@eofirm.com ■http://www.eofirm.com

